


Altek

Parts Manual



Contents

| | |
|--|----|
| Introduction | 3 |
| Boom Section Valves - Single Unit | 4 |
| Boom Section Valves - Bank Mounting. | 6 |
| Boom Section Valves - Bank Connecting Rods | 6 |
| Boom Section Valves - Bank Assembly. | 7 |
| Boom Section Valves - O-rings. | 7 |
| Spray Stop - Push-on Type | 8 |
| Spray Stop - Push-in Type | 9 |
| Nozzle Body Clamp | 10 |
| Nozzle Bodies - Dual & Quad | 11 |
| Nozzle Bodies - Direct Control - Single. | 13 |
| Nozzle Bodies - Direct Control - Dual. | 14 |
| Nozzle Bodies - Direct Control - Dual Assy | 15 |
| Nozzle Bodies | 16 |
| Fittings | 17 |
| Retaining Pins | 21 |
| Adapters | 22 |
| Tee's | 25 |
| Notes | 26 |

Contact

Goldacres

1-3 Morang Crescent,

Mitchell Park Vic 3355

P: 03 5342 6399

F: 03 5342 6308

info@goldacres.com.au

Disclaimer

Any advice or recommendations given by Goldacres, Goldacres' dealers, or employees is given in good faith and provided based on the best information available to us. No liability or responsibility is accepted or implied as a result of any information or advice tendered in this operating manual or by Goldacres its agents or employees. The end user accepts all responsibility arising from that advice. No part of this manual may be reproduced without written permission from Goldacres. All photographs and technical information remain the property of Goldacres.

Introduction

Altek GMBH designs and produces regulators, mechanical and electric ball valves, section valves and electric and pneumatic nozzle bodies as well as a full range of sprayer accessories and plug-in fittings for agricultural spray equipment.

Known for their resilient quality and modular assembly system Altek products are flexible, adaptable and make assembly and repair easy. Components can easily be configured for individual requirements. This system is now accepted as the standard by many sprayer manufacturers around the world.



All components in the Altek regulator and valve systems can be combined with each other. Altek uses two connection diameters BS36 and BS24. You can thus combine all valves and regulators in these sizes with valves and regulators of the same blank cut. Bridging adapters can join different connection diameters.

The Altek plug in range of fittings consists of both male and female adaptors in sizes up to 50mm (AS50). The system allows for connections to be connected and disconnected quickly and easily by the use of the simple safety clip.

Much of the Altek range is ideal for retrofitting to existing sprayers and equipment.

Contact Goldacres parts on 1300 301 853 for orders or to enquire about any Altek part to satisfy your requirements.

Boom Section Valves - Single Unit




Continued over page

Boom Section Valves - Single Unit

| Pos. | Part No. | Description | Qty. |
|------|-----------|--|------|
| A | GA5065515 | Boom valve assembly, Single, AS24, 3 wire, with connector (Includes plunger assembly - Part B) | - |
| B | GA2000262 | Plunger assembly, Boom valve | - |
| 1 | GA2000266 | Switch unit, 3 wire, Weatherpack plug, Boom Valve | 1 |
| 2 | GA5065695 | Retaining pin, Suit AS24 plumbing fittings | 2 |
| 3 | GA2000269 | Plug, AS24, Altek, 80376 | 1 |
| 4 | GA5065840 | O ring, 18.0 x 2.5 mm | 1 |
| 5 | GA5065701 | Retaining pin, Suit AS30 plumbing fittings | 3 |
| 6 | GA2000267 | Valve body, Boom Valve | 1 |
| 7 | GA5053510 | O ring, 25 x 2.5 mm | 1 |
| 8 | GA5065830 | O ring, 24.3 x 4.2 mm, FPM75 | 1 |
| 9 | GA5012507 | O Ring 55.25 x 2.62 mm | 2 |
| 10 | GA5065825 | Manifold piece, Boom valve | 1 |
| 11 | GA5065830 | O ring, 24.3 x 4.2 mm, FPM75 | 1 |
| 12 | GA5065835 | Plug in adapter, AS30 x AS24 | 1 |
| 13 | GA5001067 | O Ring 17.1 x 2.6 mm | 1 |
| 14 | GA5065640 | Hose barb, AS24 female x 20mm hose | 1 |
| 15 | GA2000263 | Plunger rod, Boom valve | 1 |
| 16 | GA5054650 | Circlip, Boom Valve | 2 |
| 17 | GA5054640 | Washer 17.8 x 6.1 x 1 mm | 2 |
| 18 | GA5054645 | Rubber Plunger Seal, Boom Valve | 2 |
| 19 | GA5025250 | O-ring, seal, 6 x 2 mm, FPM75, suit boom valve | 2 |
| 20 | GA2000264 | Plunger spring cap, Boom valve | 2 |
| 21 | GA2000265 | Plunger spring, Boom valve | 1 |

Boom Section Valves - Bank Mounting



| Pos. | Part No. | Description | Qty. |
|------|-----------|---|------|
| 1 | GA5065515 | Valve, Boom Section, Single, AS24, 3 wire, with connector | 3 |
| 2 | GA5065810 | End cap, Altek boom valve | 2 |
| 3 | GA5065800 | Altek boom valve mounting bracket | 2 |
| 4 | GA4582160 | Plumbing adaptor, Plug, AS40 male x G1/4" Female Thread | 1 |
| 5 | GA5065620 | Hose barb, Elbow, 90 degree, AS40 x 33mm hose barb | 1 |
| 6 | GA5065805 | Connecting Rod, M8 x 220mm, Suit 3 Bank (303 SS) | 2 |
| 7 | GA5003643 | Washer 8mm Flat SS HD | 12 |
| 8 | GA5011499 | Nut M8 ZP | 8 |
| 9 | GA5004711 | Bolt M8 x 25 GR8.8 ZP | 4 |
| 10 | GA5004917 | Nut M8 Nyloc ZP | 4 |
| 11 | GA5048385 | O ring, 42.5 x 2.62 mm, BS131, suit 2" hose barb | 1 |
| 12 | GA5012507 | O Ring 55.25 x 2.62 mm | 2 |

Boom Section Valves - Bank Connecting Rods



| Part No. | Description |
|-----------|---|
| GA5065805 | Connecting Rod suits 3 bank, 303 SS, M8 x 20 mm thread, 220 mm length |
| GA4562055 | Connecting Rod suits 4 bank, 303 SS, M8 x 20 mm thread, 280 mm length |
| GA4562125 | Connecting Rod suits 5 bank, 303 SS, M8 x 20 mm thread, 330 mm length |
| GA4562050 | Connecting Rod suits 6 bank, 303 SS, M8 x 20 mm thread, 380 mm length |
| GA4562045 | Connecting Rod suits 7 bank, 303 SS, M8 x 20 mm thread, 430 mm length |
| GA4562040 | Connecting Rod suits 8 bank, 303 SS, M8 x 20 mm thread, 480 mm length |

Boom Section Valves - Bank Assembly





| Part No. | Description |
|-----------|------------------------------------|
| GA5065740 | Section valve assembly - 3 section |
| GA5065741 | Section valve assembly - 4 section |
| GA5065704 | Section valve assembly - 5 section |
| GA5065705 | Section valve assembly - 6 section |
| GA5065706 | Section valve assembly - 7 section |
| GA5065710 | Section valve assembly - 8 section |

Boom Section Valves - O-rings




| Part No. | Description |
|-----------|---------------------------------------|
| GA5012507 | O Ring 55.25 x 2.62 mm |
| GA5048385 | O ring, 42.5 x 2.62 mm, BS131 |
| GA5065820 | O ring, 38 x 3 mm, Suit AS40 fittings |
| GA5065815 | O ring, 35 x 4 mm, Suit AS40 fittings |
| GA5053520 | O ring, 59 x 2.5 mm, NBR 70 |
| GA5001067 | O ring, 17.12 x 2.62 mm |

Spray Stop - Push-on Type




| Pos. | Part No. | Description | Qty. |
|------|-----------|---|------|
| - | GA5065520 | Spray Stop, RapidFire, Suit Teejet nozzle body, Altek | - |
| 1 | GA5053731 | End Cap with Breather | 1 |
| 2 | GA5053732 | Spring, 10 Bar | 1 |
| 3 | GA5053733 | Piston | 1 |
| 4 | GA5053734 | Valve Body | 1 |
| 5 | GA5053735 | O-ring external | 1 |
| 6 | GA5053736 | Plunger | 1 |

Spray Stop - Push-in Type





| Part No. | Description | Qty. |
|-----------|-------------------------------|------|
| GA5065520 | Spray Stop, 6mm, Rapidfire | - |
| GA5053731 | End Cap with Breather | 1 |
| GA5053732 | Spring, 10 Bar | 1 |
| GA5053733 | Piston | 1 |
| GA5053734 | Valve Body | 1 |
| GA5053735 | O-ring external | 1 |
| GA5053736 | Plunger | 1 |
| GA5053737 | Nut ring, 4 x 10 x 4.2 mm FPM | 1 |
| GA5053738 | O ring, 3.68 x 1.78 mm FPM 75 | 1 |
| GA5053742 | O ring, 16 x 1.5 mm | 2 |
| GA5053743 | O ring, 9 x 2.5 mm | 1 |
| GA5053744 | O ring, 6.02 x 2.62 mm | 1 |

Nozzle Body Clamp



| Part No. | Description | Qty. |
|-----------|--|------|
| GA5065900 | Clamp, Dual Nozzle Body, suit 3/4" Boom Poly, Includes Screw, Nut & O Ring | - |
| GA2000133 | Clamp, Dual Nozzle Body, suit 1" Boom Poly, Includes Screw, Nut & O Ring | - |
| GA5025235 | Screw, M6, Nozzle body clamp, Altek | 1 |
| 82481 | Nozzle body clamp, Upper section, Altek | 1 |
| GA5025240 | O-ring, 9.5 x 3 mm EPDM, Nozzle body clamp, Altek | 1 |
| GA5004427 | Nut M6 SS | 1 |
| 47915 | Pin, Nozzle body clamp, Altek | 1 |
| 82410 | Nozzle body clamp, Lower section, Altek | 1 |
| GA5025245 | O-ring, 19 x 2.65 mm FPM80, Nozzle body clamp, Altek | 1 |

Nozzle Bodies - Dual & Quad




Continued over page

Nozzle Bodies - Dual & Quad


| Part No. | Description | Qty. |
|-----------|--|------|
| GA5070710 | Nut Flange Plastic M8 x 1.25 | 1 |
| GA5004085 | Bolt M8 x 20 GR8.8 ZP | 1 |
| GA5065845 | Nozzle body, Twin/dual, Air shut off, 3/4" | - |
| GA5065850 | Nozzle body, Quad, Air shut off, 3/4" | - |
| GA5065900 | Nozzle body clamp, suit 3/4" Boom poly, Includes Screw, Nut and O-ring | 1 |
| GA2000133 | Nozzle body clamp, suit 1" Boom poly, Includes Screw, Nut and O-ring | 1 |
| GA5055115 | U clip, 20 x 40 x 3 mm | 1 |
| GA5065875 | Top cap | 2 |
| GA5065840 | O ring, 18.0 x 2.5 mm | - |
| GA5065880 | Spring | 2 |
| GA5065885 | Plunger | 2 |
| GA5078497 | O ring, 23.5 x 2.6, FPM80 | - |
| GA5065870 | Outer body housing | 1 |
| GA5065855 | U-Clip | 2 |
| GA5065865 | Outlet, Valve inner, Nozzle body | 2 |
| GA5065860 | Hose barb, Air fitting, 6mm hose x male thread, includes seal | 2 |
| GA5055110 | U Clip 30 x 41 x 2.5 mm | 1 |
| GA5065895 | Shutoff Plug | 1 |
| GA5053739 | O ring, 5.6 x 1.8 FPM | 2 |
| GA5053740 | Retaining disk, 11.8 x 6.8 x 2 mm | 2 |
| GA5053741 | Lip seal, 6 x 12 x 4.2 mm FPM | 2 |

Nozzle Bodies - Direct Control - Single




| Part No. | Description | Qty. |
|-----------|--|------|
| GA5065525 | Spray Stop, 6mm, Rapidfire | - |
| GA5053731 | End Cap with Breather, suit GA5065520 Spray Stop, Altek | 1 |
| GA2000172 | Circlip, Spray stop | 1 |
| GA5053732 | Spring, 10 Bar, suit Spray Stop, Altek | 1 |
| GA2000166 | Single nozzle body assembly, Direct control, Deutsch connector | 1 |
| 83224 | Spray stop - Not available as spare part | 1 |
| 84033 | Breather retainer - Not available as spare part | 1 |
| 84003 | Breather - Not available as spare part | 1 |
| GA2000168 | Inlet cartridge, 6mm, Plastic, Includes O-ring | 1 |
| GA2000169 | Outlet cartridge, 4mm, Plastic, Includes O-ring | 1 |

Nozzle Bodies - Direct Control - Dual





| Part No. | Description | Qty. |
|-----------|---|------|
| GA5065846 | Spray Stop, Nozzle body, Twin, dual, Solenoid Direct control Multi-Spray master, Air shut off, 3/4" | - |
| GA5070710 | Nut Flange Plastic M8 x 1.25 | 1 |
| GA5004085 | Bolt M8 x 20 GR8.8 ZP | 1 |
| GA5065900 | Nozzle body clamp, suit 3/4" Boom poly, Includes Screw, Nut and O-ring | 1 |
| GA2000133 | Nozzle body clamp, suit 1" Boom poly, Includes Screw, Nut and O-ring | 1 |
| GA2000165 | Dual nozzle body assembly, Direct control | 1 |
| GA5055115 | U clip, 20 x 40 x 3 mm, 82297, Suit Altek nozzle body GA5065845 | 1 |

Nozzle Bodies - Direct Control - Dual Assembly



| Part No. | Description | Qty. |
|-----------|--|------|
| GA5078544 | Dual solenoid valve, including 200mm cables & Deutsch connectors | 1 |
| GA5065870 | Housing Multi-Spray 2-Nozzle | 1 |
| GA5053739 | O ring, 5.6 x 1.8 FPM | 2 |
| GA5053740 | Stainless washer | 2 |
| GA5053741 | Lip Seal 6 x 12 x 4.2 mm | 2 |
| GA5065865 | Nozzle holder 5° complete, 0°, 0° | 2 |
| GA5065855 | U-Clip AS20 | 2 |
| GA5065885 | Stainless piston complete with O-ring | 2 |
| GA5078497 | O-ring, 23.5 x 2.6 mm, FPM80 | - |
| GA5065880 | Spring | 2 |
| GA5065875 | Cylinder Cap | 2 |
| GA5065895 | Blanking Plug | 1 |
| GA5055110 | U-clip 30 x 41 x 2.5 mm | 1 |
| GA5078547 | Seal, White PVC | 4 |
| GA5078545 | Breather insert, 25.5 x 12 x 12 mm | 1 |
| GA5078546 | Circlip, 26 x 1.2 mm | 1 |
| GA5078548 | Push fitting, Air line, 6mm | 2 |


Nozzle Bodies



| Pos. | Part No. | Description |
|------|-----------|---------------------------------------|
| A | GA5065820 | O ring, 38 x 3 mm, Suit AS40 fittings |
| B | GA5065815 | O ring, 35 x 4 mm, Suit AS40 fittings |
| C | GA5065605 | Plug in adapter, AS40 x AS24 |

| Pos. | Part No. | Description |
|------|-----------|---|
| 1 | GA5065530 | Valve, Ball, 5 x AS40 female inlet / outlets, Lever handle |
| 2 | GA5022482 | SHCS M10 x 35 GR I2.9 ZP |
| 3 | GA5065531 | Handle, Red plastic, Suit 5 way ball valve |
| 4 | GA5065500 | Relief Valve, pressure control, AS40, 10 bar 145 PSI |
| 5 | GA5065550 | Valve, Quick Fit, 2 Way, Electric |
| 6 | GA5065545 | Valve, Quick fit flip top, 2 way, AS40 male x AS24 female x AS40 female |

Fittings



| Pos. | Part No. | Description |
|------|-----------|------------------------|
| 1 | GA5065770 | Fitting, G1.25 male |
| 2 | GA5065775 | Nut, G2 3/4" |
| 3 | GA5065780 | Fitting, G2 female |
| 4 | GA5065785 | Fitting, G1.5 female |
| 5 | GA5065760 | Fitting, G2 male short |
| 6 | GA5065755 | Fitting, G2 male long |
| 7 | GA5065765 | Fitting, G1.5 male |

Fittings



| Pos. | Part No. | Description |
|------|-----------|---------------------------------------|
| A | GA5065820 | O ring, 38 x 3 mm, Suit AS40 fittings |
| B | GA5065815 | O ring, 35 x 4 mm, Suit AS40 fittings |
| 1 | GA5065575 | Hose barb, Straight, AS40 x 20mm hose |
| 2 | GA5065580 | Hose barb, Straight, AS40 x 25mm hose |
| 3 | GA5065585 | Hose barb, Straight, AS40 x 33mm hose |
| 4 | GA5065590 | Hose barb, Straight, AS40 x 39mm hose |

Fittings

1



2



3




4



5



6



| Pos. | Part No. | Description |
|------|-----------|------------------------------------|
| 1 | GA5065630 | Hose barb, AS20 female x 12mm hose |
| 2 | GA5065635 | Hose barb, AS20 female x 17mm hose |
| 3 | GA5065745 | Hose barb, AS24 female x 15mm hose |
| 4 | GA5065640 | Hose barb, AS24 female x 20mm hose |
| 5 | GA5065645 | Hose barb, AS40 female x 20mm hose |
| 6 | GA5065650 | Hose barb, AS40 female x 25mm hose |

Fittings


1



2



3



4



5




6




| Pos. | Part No. | Description |
|------|-----------|---|
| A | GA5065820 | O ring, 38 x 3 mm, Suit AS40 fittings |
| B | GA5065815 | O ring, 35 x 4 mm, Suit AS40 fittings |
| 1 | GA5065655 | Hose barb, Straight, AS40 x 33mm hose |
| 2 | GA5065660 | Hose barb, Straight, AS40 x 39mm hose |
| 3 | GA5065610 | Hose barb, Elbow, 90 degree, AS40 x 20mm hose |
| 4 | GA5065615 | Hose barb, Elbow, 90 degree, AS40 x 25mm hose |
| 5 | GA5065620 | Hose barb, Elbow, 90 degree, AS40 x 33mm hose |
| 6 | GA5065625 | Hose barb, Elbow, 90 degree, AS40 x 39mm hose |

Fittings







| Pos. | Part No. | Description |
|------|-----------|---|
| 1 | GA5065750 | Hose barb, Elbow, 90 degree, AS24 x 15mm hose |
| 2 | GA5065675 | Hose barb, Elbow, 90 degree, AS24 x 20mm hose |

Retaining Pins





| Pos. | Part No. | Description |
|------|-----------|---------------------|
| 1 | GA5065695 | Retaining pin, AS24 |
| 2 | GA5065701 | Retaining pin, AS30 |
| 3 | GA5065690 | Retaining pin, AS40 |

Adapters



| Pos. | Part No. | Description |
|------|-----------|--|
| A | GA5065820 | O ring, 38 x 3 mm, Suit AS40 fittings |
| B | GA5065815 | O ring, 35 x 4 mm, Suit AS40 fittings |
| C | GA5001067 | O ring, 17.12 x 2.62 mm |
| D | GA5065830 | O ring, 24.3 x 4.2 mm, FPM75 |
| 1 | GA5065835 | Plug in adapter, AS30 x AS24 |
| 2 | GA5065605 | Plug in adapter, AS40 x AS24 |
| 3 | GA4582400 | Cap Altek AS40 with 1/4" BSPP Female Thread (Delron) |
| 4 | GA4582405 | Cap Altek AS40 with 1/2" BSPP Female Thread (Delron) |
| | GA4582410 | Cap Altek AS40 with 3/4" BSPP Female Thread (Delron) |
| 5 | GA5065680 | Plug, AS40 male |
| 6 | GA5065735 | Plumbing adaptor, AS40 male x AS40 male |


Adapters



| Pos. | Part No. | Description |
|------|-----------|--|
| A | GA5065820 | O ring, 38 x 3 mm, Suit AS40 fittings |
| B | GA5065815 | O ring, 35 x 4 mm, Suit AS40 fittings |
| 1 | GA5065595 | Plumbing adaptor, AS40 male x 1-1/4" male thread |
| 2 | GA5065600 | Plumbing adaptor, AS40 male x 1" male thread |
| 3 | GA5065665 | Plumbing adaptor, AS40 female x 1" male thread |
| 4 | GA5065670 | Plumbing adaptor, AS40 female x 1-1/2" male thread |
| 5 | GA4582415 | Plumbing adaptor, AS24 female x 3/4" male thread |


Adapters

①



NOTE: 1" NPT thread suits Raven regulator valve

②



③



④



⑤



| Pos. | Part No. | Description |
|------|-----------|--|
| A | GA5065820 | O ring, 38 x 3 mm, Suit AS40 fittings |
| B | GA5065815 | O ring, 35 x 4 mm, Suit AS40 fittings |
| 1 | GA4582385 | Coupling, AS40 female x 1" NPT male thread |
| 2 | GA4582160 | Plumbing adaptor, Plug, AS40 male x 1/4" female thread |
| 3 | GA4582300 | Coupling Altek AS40 Female to Female (Delron) |
| 4 | GA4582395 | Plumbing Fitting, Cap, AS40 |
| 5 | GA4582345 | Dummy plug AS40 x 1/2" female (45mm Delron) |

Tee's

1




2



3




4



| Pos. | Part No. | Description |
|------|-----------|---|
| 1 | GA5065555 | Tee, 3 Port, AS40 female, no M8 inserts |
| 2 | GA5065560 | Tee, 3 Port, AS40 female, M8 inserts |
| 3 | GA5065565 | Tee, 4 Port, AS40 female, no M8 inserts |
| 4 | GA5065570 | Tee, 4 Port, AS40 female, M8 inserts |

Notes

Notes



GOLDACRES

www.goldacres.com.au