

Specifications

Feature	Description	2500	3000
Rinse tank	Rear mounted, fill via fill manifold	100L	180L
Hand wash tank	Mounted on LHS with soap dispenser	25L	
Chassis	Fully welded modular construction 125 x 75 x 6mm RHS Single beam bolt on drawbar with forged tow eye	Std	Std
Axle	Rigid axle 70mm. 1800mm width (other widths on request)	Std	Std
Wheels and Tyres	14.9 x 24	Std	N/A
	420/85R34	N/A	Std
	540/65R28	Opt	Opt
	320/90R42	Opt	N/A
	380/90R46	N/A	Opt
Mudguards	Full length poly mudguards with mud flaps	Opt	Opt
3PL Hitch	3PL turnable hitch	Opt	Opt
Rate Controller	3-way electric with electric regulation	Std	N/A
	Raven SCS450	Opt	Std
	Raven SCS450 - No Console	Opt	Opt
	IsoBus Control	Opt	Opt
Paint	Grit blasted steel work followed by high build primer. All welded sections seam sealed wet top coat paint system with low temperature baked finish	Std	Std
Spray Pump	140 l/min with PTO	Std	N/A
	170 l/min with PTO	Opt	Std
	Hydraulic drive	Opt	Opt
Filtration	1 x suction, 2 x pressure & nozzle filters	Std	Std
Water transfer	2" integrated fill point with EZ control	Std	Std
Hydraulics	Hydraulics required: <ul style="list-style-type: none">1 set for lift/lower1 set for fold in/out1 set for spray pump if hydraulic drive optioned2 sets for boom wing tilt if optioned		
	Electric over hydraulic spool valves. (2 sets of remotes required) Hydraulic manifold to operate 4 functions with switch box. Open or closed centre system	Opt	Opt

Scan to view full specs.



The policy of Goldacres is one of continuous development and improvement. Goldacres reserve the right to alter any specifications, designs and prices of the range shown without notice and without incurring any obligation regarding such changes. The pictures and information shown or referred to in this publication are a general guide only. Should you purchase the items from this publication the publication does not form part of the contractual arrangements with Goldacres. The purchase of any item of equipment is subject to the Goldacres Terms and Conditions of sale. 07/25 - GA8702379

Feature	Description	2500	3000
Main tank drain	1.5" remote operated	Std	N/A
	2" remote operated	N/A	Std
Tank rinse nozzles	Single rotating	Std	N/A
	Twin rotating	N/A	Std
Booms	Delta 12m,15m,18m, 21m & 24m	Opt	N/A
	Delta 18m, 21m & 24m	Opt	Opt
	3d breakaway	Opt	Opt
	Boom end protectors	Opt	Opt
	Individual wing tilt	Opt	Opt
	Trijets – Turret design	Opt	Opt
Boom sections	Electric operated fence line nozzles	Opt	Opt
	3 equal width section	Opt	Opt
	4 or 5 sections	Opt	Opt
Induction	27L chemical induction hopper	Opt	Opt
	Transcal	Opt	Opt
	Micromatic rinse socket & coupler	Opt	Opt
Foam marker	57L double sided	Opt	Opt
Gross weights (kg)	2500L	2150	
	3000L		2726

*Weights based on no fluids in tank: 2500L with 18m boom, 3000L with 21m boom.



PS 2500-3000



Pasture, broadacre & rowcrop specialist.



Why choose PS sprayers?

- Industry's toughest hydraulic folding Delta boom - unmatched stability.
- Effortless operation with simple, intuitive control systems
- Reinforced RHS chassis for long-lasting durability
- Designed, built and backed right here in Australia.

The ultimate spraying solution - Built for Aussie farms, engineered for performance.
Proven design. Built on 45+ years of Aussie spraying innovation.

The small frame Prairie Special comes in two tank capacities, 2500L & 3000L with fully hydraulic Delta booms ranging from 12 to 24m in width, large diameter

single wheel options coupled with multiple boom plumbing configurations and a simple to use control system suitable to many cropping applications.

Configurations



Multiple axle widths, plumbing configurations, wheel equipment and connections are available to suit rowcrop or broadacre spraying.

Control



Fast, frustration-free operation at your fingertips - clearly labeled controls and flip valves make spray setup and filling quick and hassle-free.

Induction hopper: Easily mix granules and liquids for precise chemical induction.

Delta Booms

- Delta 3-way suspension system delivers industry-leading boom ride and ultra-smooth spraying, even in rough terrain - minimising wear and improving accuracy.
- Hydraulic lift and fold with tilt optional, featuring the industry leading "Delta" three way suspension system for unmatched boom stability.
- Available in sizes
 - 12, 15, 18, 21 & 24m on 2500L models.
 - 18, 21 & 24m on 3000L models.

Rate control

Choose from 3-way electric (2500L model) or boost accuracy and save input costs with Auto rate control - ensuring consistent application with varying speed and terrain.

